

Reductor Corona Sinfin

NMRV Tamaño 30



mairsa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 030	5	350	159	1.02	113
	7.5	233	159	0.69	129
	10	175	159	0.54	142
	15	117	159	0.38	163
	20	88	159	0.30	179
	25	70	186	0.30	193
	30	58	177	0.25	205
	40	44	159	0.19	225
	50	35	150	0.15	243
	60	29	142	0.13	259
80	22	115	0.09	284	

Dimensiones	Pulgadas
A	2.48
AB	2.15
AC	1.57
AJ	2.68
AJ1	2.56
AK	1.97
AK1	2.17
AQ	3.15
B	2.20
B2	5.83
BA	0°
BB	0.16
BD	3.15
BE	0.24
BF	.26, 4 pl.
BR	2.95
BU	M6 Tap 0.43 deep, 4 pl.
CA	45°
CE	2.76
DY	2.24
E	2.13
EA	2.64
F	1.73
G	0.22
H	0.26
K	1.26
O	3.82
R	0.70
RB	0.42
RH	0.71
S	0.188
SB	0.094
SH	0.188
U	0.625
UH	0.625
UT	1/4-20
V	1.58
VA	1.67
VB	0.827
VN	1.18
WG	1.14
UB	0.375
UR	-
Y	1.18
YE	1.06
YF	2.17
Clave de entrada	
Longitud	0.875
Cuadrado	0.094
Clave de salida	
Longitud	1.125
Cuadrado	0.188
Peso (lb)	3

