

Reductor Corona Sinfin

NMRV Tamaño 40



mairsa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 040	5	350	301	1.88	221
	7.5	233	354	1.51	253
	10	175	354	1.16	279
	15	117	354	0.80	319
	20	88	345	0.61	350
	25	70	336	0.50	378
	30	58	398	0.53	403
	40	44	363	0.39	441
	50	35	345	0.31	476
	60	29	319	0.25	507
80	22	292	0.19	556	
100	18	257	0.15	595	

Dimensiones	Pulgadas
A	3.07
AB	2.64 (3.82)
AC	1.97
AJ	2.95 (3.43)
AJ1	2.95
AK	2.36
AK1	2.36
AQ	3.94
B	2.80
B2	7.24
BA	45°
BB	0.16
BD	4.33
BE	0.28
BF	35, 4 pl.
BR	3.43
BU	M6 Tap 0.32 deep, 4 pl.
CA	45°
CE	3.74
DY	2.81
E	2.76
EA	3.15
F	2.36
G	0.26
H	0.26
K	1.26
O	4.78
R	0.83
RB	0.55
RH	0.84
S	0.188
SB	0.125
SH	0.188
U	0.750
UH	0.750
UT	1/4-20
V	1.97
VA	2.09
VB	1.024
VN	1.18
WG	1.44
UB	0.500
UR	1/4-20
Y	1.58
YE	1.38
YF	2.17
Clave de entrada	
Longitud	0.875
Cuadrado	0.125
Clave de salida	
Longitud	1.500
Cuadrado	0.188
Peso (lb)	5

