

Reductor Corona Sinfin

NMRV Tamaño 50



mairsa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 050	5	350	549	3.43	322
	7.5	233	628	2.64	369
	10	175	637	2.06	406
	15	117	655	1.48	464
	20	88	646	1.14	510
	25	70	619	0.90	551
	30	58	743	0.96	586
	40	44	672	0.70	643
	50	35	646	0.57	694
	60	29	602	0.47	739
	80	22	575	0.38	810
100	18	487	0.28	866	

Dimensiones	Pulgadas
A	3.62
B	3.31
BA	3.35
BC	3.94
BH	45 ∞
BK	2.756 $^{+0}_{-0.0018}$
BL	M8x10
C	1.97
D	2.36
E	3.15
F	2.76
G	0.28
H	0.33
J	4.76
K	1.93
L	3.35
M	3.43
N	1.57
O	5.67
P	3.54
Q	2.91
T	2.52
Z	3.92
RH	1.11
SH	0.25
UH	1 $^{+0.001}_{-0}$
VB	1.18
R	1.11
S	0.25
U	1 $^{+0}_{-0.0005}$
U KEY	0.250x1.500
UT	03/08/2016
V	1.97
VA	2.11
Y	7.83
AB	3.54
AF	0.35
AG	0.2
AK	2.756 $^{+0.0018}_{-0}$
Clave de entrada	
Longitud	0.875
Cuadrado	0.094
Clave de salida	
Longitud	1.125
Cuadrado	0.188
Peso (lb)	3

