

Reductor Corona Sinfín

NMRV Tamaño 75



mairisa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 075	7.5	233	1637	6.81	549
	10	175	1725	5.45	604
	15	117	1770	3.86	691
	20	88	1858	3.15	759
	25	70	1770	2.46	820
	30	58	2035	2.48	873
	40	44	1947	1.88	957
	50	35	1858	1.50	1033
	60	29	1770	1.26	1099
	80	22	1681	0.97	1205
100	18	1593	0.80	1289	

Dimensiones	Pulgadas
A	4.72
AB	4.37
AC	3.39
AJ	6.49
AJ1	4.53
AK	5.12 ⁺⁰ _{-0.0001}
AK1	3.74 ⁺⁰ _{-0.0021}
AQ	6.77
B	4.41
B2	10.51
BA	45°
BB	0.24
BD	7.87
BE	0.51
BF	.55, 4 pl.
BR	5.51
BU	M8 Tap 0.55 deep, 8 pl.
CA	45°
CE	6.69
DY	4.69
E	4.72
EA	4.96
F	3.54
G	0.39
H	0.45
K	2.64
O	8.07
R	1.36
RB	0.96
RH	1.37
S	0.250
SB	0.188
SH	0.250
U	1.250 ⁺⁰ _{-0.0005}
UH	1.250 ^{+0.001} ₋₀
UT	1/2-13
V	2.76
VA	2.89
VB	1.575
VN	2.36
WG	2.24
UB	0.875
UR	1/4-20 ⁺⁰ _{-.0005}
Y	2.95
YE	2.36
YF	3.66
Clave de entrada	
Longitud	1.875
Cuadrado	0.188
Clave de salida	
Longitud	2.250
Cuadrado	0.250
Peso (lb)	20

