

Reductor Corona Sinfín

NMRV Tamaño 110



mairsa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 110	7.5	233	4247	17.48	776
	10	175	4601	14.36	853
	15	117	5043	10.86	976
	20	88	4955	8.10	1073
	25	70	5220	6.90	1158
	30	58	5574	6.53	1233
	40	44	5397	4.81	1352
	50	35	5309	3.93	1459
	60	29	4955	3.19	1553
	80	22	4336	2.25	1703
100	18	4070	1.79	1821	

Dimensiones	Pulgadas
A	6.10
AB	5.16
AC	5.02
AJ	9.06
AJ1	6.50
AK	6.69 ⁰ _{-0.0001}
AK1	5.12 ⁺⁰ _{-0.0025}
AQ	9.94
B	5.67
B2	16.14
BA	45°
BB	0.24
BD	11.02
BE	0.59
BF	.55, 8 pl.
BR	7.87
BU	M10 Tap 0.71 deep, 8 pl.
CA	45°
CE	10.24
DY	6.59
E	6.69
EA	6.81
F	4.53
G	0.57
H	0.55
K	2.91
O	11.61
R	1.79
RB	1.24
RH	1.80
S	0.375
SB	0.250
SH	0.375
U	1.625 ⁺⁰ _{-0.0005}
UH	1.625 ^{+0.001} ₋₀
UT	5/8-11
V	3.54
VA	4.13
VB	1.969
VN	2.76
WG	2.91
UB	1.125
UR	3/8-16 ⁺⁰ _{-0.0005}
Y	4.33
YE	3.35
YF	4.92
Clave de entrada	
Longitud	2.250
Cuadrado	0.250
Clave de salida	
Longitud	2.750
Cuadrado	0.375
Peso (lb)	77

