

Reductor Corona Sinfín

NMRV Tamaño 130



mairsa



Modelo	Radio	RPM	Torque (in-lbs)	Max HP	OHL (lbs)
NMRV 130	7.5	233	6636	27.01	1017
	10	175	7255	22.64	1119
	15	117	8140	17.33	1279
	20	88	8052	13.00	1407
	25	70	8229	10.88	1518
	30	58	9202	10.65	1616
	40	44	9290	8.27	1772
	50	35	8671	6.42	1913
	60	29	7963	5.12	2036
	80	22	7432	3.79	2233
100	18	6548	2.84	2387	

Dimensiones	Pulgadas
A	6.69
AB	5.51
AC	5.81
AJ	10.03
AJ1	8.46
AK	7.09 ⁰ _{-0.0001}
AK1	7.09 ⁺⁰ _{-0.0025}
AQ	11.52
B	6.10
B2	14.17
BA	45°
BB	0.28
BD	12.60
BE	0.59
BF	.63, 8 pl.
BR	9.84
BU	M12 Tap 0.83 deep, 8 pl.
CA	22.5°
CE	11.42
DY	7.38
E	7.87
EA	7.60
F	4.72
G	0.61
H	0.63
K	--
O	13.19
R	1.92
RB	1.36
RH	1.93
S	0.375
SB	0.250
SH	0.375
U	1.750 ⁺⁰ _{-0.0005}
UH	1.750 ^{+0.001} ₋₀
UT	5/8-11
V	3.54
VA	3.74
VB	2.362
VN	3.15
WG	3.19
UB	1.250
UR	1/2-13 ⁺⁰ _{-0.0005}
Y	5.12
YE	3.94
YF	5.51
Clave de entrada	
Longitud	2.500
Cuadrado	0.250
Clave de salida	
Longitud	2.750
Cuadrado	0.375
Peso (lb)	106

