


# Reductor de Velocidad Doble Reducción

NMRVD50/63



Modelo	Relacion	RPM	Torque (in-lbs)	Max HP
NMRVD50/63 150:1	150	11.67	10,804	2
NMRVD50/63 200:1	200	8.75	14,406	2
NMRVD50/63 250:1	250	7.00	18,007	2
NMRVD50/63 300:1	300	5.83	21,609	2
NMRVD50/63 400:1	400	4.38	28,811	2
NMRVD50/63 500:1	500	3.50	18,007	1
NMRVD50/63 600:1	600	2.92	21,609	1
NMRVD50/63 750:1	750	2.33	20,258	0.75
NMRVD50/63 900:1	900	1.94	24,310	0.75
NMRVD50/63 1200:1	1200	1.46	21,609	0.50
NMRVD50/63 1500:1	1500	1.17	27,011	0.50
NMRVD50/63 1800:1	1800	0.97	16,206	0.25
NMRVD50/63 2400:1	2400	0.73	21,609	0.25
NMRVD50/63 3000:1	3000	0.58	27,011	0.25
NMRVD50/63 4000:1	4000	0.44	36,014	0.25
NMRVD50/63 5000:1	5000	0.35	45,018	0.25



Tamaño	A	G	G1	H	H1	I	R	H2	I2	N2	R2	Z
NMRVD50/63	4.72"	3.14"	4.72"	3.38"	3.50"	2.95"	4.68"	2.36"	1.96"	1.71"	3.30"	7.69"

